

Clarksville-Montgomery County School System RECOMMENDED ROOF WORK SAFETY CHECKLIST

Roof Work Safety Preparations:	Complete or N/A
1. Pre-Job Safety Review Conducted for Non-Routine Job	
2. Safe Job Procedure Reviewed for Routine Job	
3. Check In / Check Out System	
4. Minimum of Two Persons Performing Work	
5. Lighting Provided for Night Work	
6. Safe Weather Conditions	
7. Falling Object Protection Provided	
8. Fall Prevention / Protection System Provided:	
8.1. Warning Line System for Flat or Low Sloped Roof	
8.2. Temporary Standard Railing Installed	
8.3. Personal Fall Protection Required	
8.4. Anchor Points Designated	
9. Roof Holes Covered or Guarded with Standard Railing	
10. Rules for Use of Mechanical Equipment Reviewed	
11. Evaluate Roof Loading – Added Support Required?	

Roof Work Rule Reminders:

- 1. Warning line systems are only allowed as fall prevention on flat or *low sloped roofs* when the work takes place six feet or more from the roof edge or opening. The use of mechanical equipment may require additional distance from the edge or opening; refer to the complete rules.
- 2. When work on a flat or low sloped roof takes place less than six feet from the roof edge or opening, standard railing with toe boards or personal fall protection systems must be used.
- 3. Standard railing or personal fall protection systems must be used on *steep sloped roofs* regardless of the distance from the roof edge or opening.

4/15/11, Rev. B RSK-F007 Page 1 of 1