Location:	
Date/Time:	

## School Bus Service & Inspection Form

Unit Number:	
Mileage:	
Repair Order #:	

$\checkmark$ = Okay	X = Attention Required	R = Repaired	N/A = Not Applicable
		r	

	11/11 - 110t ripplicable			
	OK	Repaired	N/A	
Start engine. Check operation of the following:		1		
a. Clutch pedal free play, if applicable. Should be 1" to 2"				
b. Check hydraulic fluid level.				
Inspect condition of windshield Side glasses Mirror				
Inspect condition of windshierdSide grasses ivintor      Inspect condition of wiper blades Fill washer container				
4. Check condition on all Belts Fan Drive Alternator				
<ul> <li>5. Inspect engine mounts – condition and security.</li> <li>6. Check air cleaner restriction indicator. Service filter if necessary.</li> </ul>		<del>                                     </del>		
		<del> </del>		
7. Inspect cooling system for leaks – Radiator Hoses Hoses				
8. Check coolant level test PH and document readings.				
9. Replace coolant filter if equipped (at 30,000 miles).				
10. Check Hydraulic fluid level (power steering, brake & wheelchair lift)				
11. Grease rear suspension Drive shaft Brake mechanism				
12. Check lube level – Rear End Trans. (std.)				
13. Inspect brake lining wear: Rear replace is less than 1/4" thick.				
Front replace if within 1/8" of rivet head.				
14. Clean rear axle vent.				
15. Inspect rear springs, broken leaves Loose U-bolts				
16. Inspect battery installation, hold-down clamps security.				
17. Inspect battery cables for corrosion, chafing. Fill, if applicable.				
18. Inspect fuel tank mounting brackets for cracks, security.				
19. Grease suspension, kingpin & steering linkage fitting using grease gun.				
20. Check lube-level of front wheels.				
21. Inspect front springs for broken leaves Loose U-bolts Shackles				
22. Grease brake mechanism Check brake lining wear				
23. Inspect steering gear box mounting for security.				
24. Inspect wheel/rim lug nuts for security.				
25. Inspect wheels/rims for cracks, slipping.				
26. Inspect tires for cuts, tread depth, wear.				
27. Inflate tires to recommended pressure.				
28. Change engine oil Replace oil filters				
29. Replace fuel filters				
30. Start engine. Check filters for leaks. Recheck engine oil level.				
31. Check automatic transmission fluid level.				
32. Wipe grease off steering wheel and driver's seat.				
33. Check tie rods and drag links.				
34. Raise bus; check kingpins according to the manufacturer's instructions.				
35. Inspect exhaust system, air leaks, grease seals, etc.				
36. Change transmission filters and fluid (at 30,000 mile interval).				
Service only units that have previously been serviced with non-synthetic fluid!				
37. Replace external transmission filter if equipped at <b>30,000 miles</b>				
38. Service transmissions equipped with synthetic fluid at 100,000 mile interval.				
39. Replace air filter (at 30,000 mile interval).				
40. Replace internal crankcase breather element at <b>60,000 miles</b> .				
41. Fill out all required work orders, forms, etc.				
Comments:	•	-		
Service Technician Signature: Mechanic/Designee Sign	nature:			

3/26/18, Rev. D VHM-F002